

# BeFit Zero

**BeFit Zero** rubber tiles bring recycled rubber to a whole new level. A revolutionary production method delivers outstanding results and sets new standards for indoor rubber tiles: **ZERO** tolerance for dimensions (0,05%)




## COMPOSITION

Recycled SBR Rubber, MDI polyurethane bonding agent, color pigments.

## SPECIFICATIONS

Ideal for Fitness centers, personal training centers, Functional training centers, etc.

Usage	Indoor
Size	100x50 cm
Thickness	15 mm / 20mm / 25mm / 30mm
Color	
Surface	Porous, soft, smooth
Density	950-980 kgs/m <sup>3</sup>
Weight/m <sup>2</sup>	14kg /18kg / 23kg / 27kg
Hardness	60 ± 3 Shore A
Tolerance (Dimensions/Thickness)	0,05% / 0,05%

## APPLICATION AREAS

Depending on the thickness selected: Indoor climbing wall areas, Fitness facilities, Functional training centers, Personal Training Studios, Crossfit Boxes, etc.

## CHOOSE YOUR THICKNESS

BeFit Zero	BeFit Zero	BeFit Zero
15 mm	20 mm	25 mm
Weights up to 60-80kg used constantly. With 14kg/m <sup>2</sup> , these tiles protect your equipment and your sub-base flooring.	Areas where power lifting is involved and dropped weights over 80kgs on a regular basis (such as in dead lift or clean-and-jerk areas). This thickness offer higher cushion and sound absorption.	Ideal for Crossfit Boxes, where weights go over 125 kgs easily. When heavier weights are used just on occasions, 20mm tiles can be used too. Professional Crossfit Boxes, should use at least 25mm thickness, especially for places where high sound isolation is imperative.

## CERTIFICATIONS

Fire Resistance	Efl (B2)a,c (EN 13501)
Reaction to Fire	Fs <150 mm in 20 seconds (ISO 11925)
Impact Sound Insulation	26 dB (ISO 10140)
Airborne Sound Insulation	48 dB (ISO 10140)
Abrasion Resistance	0,43 gr (ISO 5470-1)

**High impact resistance**  
**Superb acoustic isolation**  
**Easy cleaning and mantainance**  
**Superior performance**

The product data sheet is not subject to any change service!  
All information is without guarantee.

You can find the latest version of this document on the relevant product page at [www.bekarubber.com](http://www.bekarubber.com).